

| Version No | Specification Status | Approve date |
|------------|----------------------|--------------|
| 2 | Approved | 2009-03-12 |

| Property | Condition | UOM | Min | Max | MOM |
|-------------------|-----------|-------------|--------------------------|-------|--------------|
| Acetic acid (w/w) | Standard | % by weight | 99,3 | | SS-ISO 753-2 |
| Appearance | Standard | na | Clear, colourless liquid | | ASTM D 2090 |
| Colour (Hz) | Standard | na | | 10 | AMSE 1102 |
| Water (w/w) | Standard | % by weight | | 0,3 | SS-ISO 760 |
| Density | D 20/4 | g/ml | 1,048 | 1,052 | SS-ISO 758 |

The seller does also guarantee following properties, although not tested on each delivery:

| Property | Condition | UOM | Min | Max | MOM |
|---------------------------|-----------|----------|-----|------|-----------|
| Iron (w/V) | Standard | mg/l | | 1 | KA 12.000 |
| Sulfate (w/V) | Standard | mg/l | | 5 | KA 30.102 |
| Inorganic chloride (w/V) | Standard | mg/l | | 5 | KA 30.12 |
| Evaporation residue (w/V) | Standard | g/100 ml | | 0,01 | AMSE 1124 |